


**MODEL NO. 4415-1C**

Dimensions :



Features :

Excellent lighting effect,  
perfect glare control,  
uniform and comfortable lighting  
experience

**Luminaire**

|          |          |        |      |
|----------|----------|--------|------|
| Material | aluminum | Optics | Lens |
| Surface  | WH       |        |      |


**Technical specification**

|               |                 |     |      |
|---------------|-----------------|-----|------|
| Light source  | COB             | CCT | 3000 |
| Beam angle    | 15° / 24° / 36° | CRI | > 90 |
| Luminous flux | 250 lm          |     |      |


**Electrical specification**

|               |                  |                |         |
|---------------|------------------|----------------|---------|
| Total power   | 7W               | Control dim    | on/off  |
| Input voltage | 220-240V 50/60Hz | Output voltage | 28-42 V |
| Power factor  | 0.5              | Output current | 150mA   |


|                     |                       |                 |                        |
|---------------------|-----------------------|-----------------|------------------------|
| IP rating           | IP 20                 | Recommended use | Indoor                 |
| Installation        | RECESSED CEILING      | Adjusted        | swing 30°, rotate 355° |
| Storage Temperature | -20°C up to max. 50°C | Packing         | /                      |

**Light Distribution Curve**

| H (m) | D (m) | Em (lx) |
|-------|-------|---------|
| 1     | 0.3   | 2520    |
| 2     | 0.5   | 630     |
| 3     | 0.8   | 280     |
| 4     | 1.1   | 158     |
| 5     | 1.3   | 101     |



| H (m) | D (m) | Em (lx) |
|-------|-------|---------|
| 1     | 0.4   | 1749    |
| 2     | 0.9   | 437     |
| 3     | 1.3   | 194     |
| 4     | 1.7   | 109     |
| 5     | 2.1   | 70      |



| H (m) | D (m) | Em (lx) |
|-------|-------|---------|
| 1     | 0.6   | 1066    |
| 2     | 1.3   | 267     |
| 3     | 1.9   | 118     |
| 4     | 2.6   | 67      |
| 5     | 3.2   | 43      |

**Accessories**