
# MODEL NO.

# 4575-1U

### Dimensions:



### Features:

A linear design that integrates perfectly in any context such as the showroom








### Luminaire

| Lammanc                  |                    |                 |                         |
|--------------------------|--------------------|-----------------|-------------------------|
| Material                 | aluminum           | Optics          | /                       |
| Surface                  | ВК                 |                 |                         |
| Techinical specification |                    |                 |                         |
| Light source             | LED                | ССТ             | 2700 /3000 /4000 /5000K |
| Beam angle               | 100°               | CRI             | > 90                    |
| Luminous flux            | 300 lm             |                 |                         |
| Electrical specification |                    |                 |                         |
| Total power              | 8 W                | Control dim     | 0-10V / DALI / wireless |
| Input voltage            | DC 48V             | Output voltage  | DC 36V                  |
| Power factor             | 1                  | Output current  | 200 mA                  |
| Application              |                    |                 |                         |
| IP rating                | IP 20              | Recommended use | Indoor                  |
| Installation             | Track installation | Adjusted        | swing 90°               |
|                          |                    |                 |                         |

Packing

## **Light Distribution Curve**

Storage Temperature



| H (m) | D (m) | Em (lx) |
|-------|-------|---------|
| 1     | 2.4   | 101     |
| 2     | 4.8   | 25      |
| 3     | 7.2   | 11      |
| 4     | 9.5   | 6       |
| 5     | 11.9  | 4       |

-20°Cup to max. 50°C

### **Accessories**